

Dodge® modified mounted bearings

Solving mounted bearing relubrication issues



Solution

The immediate cause of failure was not obvious to the customer. Working with the Dodge sales engineer and engineering team, it was determined that the bearing failures were caused by grease wash out as well as preload of bearing at installation.

Dodge mounted ball bearings minimize heat build up. The design includes a simpler shaft attachment design to ensure proper installation. A patented bearing cage maintains a cooler operating temperature as well retains grease in spite of daily washdown.

Dodge Max life cage

Patented two-piece design that creates a constant grease compartment around each of the rolling elements.

- Compartments provide constant contact between balls and grease to prevent wear and minimize friction.
- Holds in the grease to prevent it from being washed out during high pressure cleaning

Challenge: Relubrication not delivering full bearing life A pumpkin processor experienced noise from a mounted ball bearing on their pulper application after only a month in service, then failure and replacement after 6-8 weeks. Recommended relubrication was not effective. With their prime operation period approaching, they needed to eliminate this downtime to meet demand.

Result

The modified bearing solution stopped grease wash out and provided an easier installation. The pumpkin processor saw downtime due to bearing failure eliminated, saving \$35,000 in lost production.



*Grey represents grease in cage

Dodge modified mounted bearings

Mounted bearings that meet your application


needs

Local manufacturing and customer service

Building Dodge mounted bearings locally, with modification capability, means that you get the bearing you need, when you need it. Being local also means that you get the availability and personal customer service you deserve.

Local sales engineers can work with you to review your specific standard bearing challenges and find the modification required for your specific application.

Dodge application engineering 864.284.5700





Sealing

- Accomodate high speeds and temperatures
- Minimize drag
- Protect bearings from harsh environments



Lubrication

- Supply specific greases and factory fill rates
- Provide bearings without grease for customer fill
- Plug bearings to reduce maintenance
- Plug bearings to avoid the addition of potentially incompatible grease by customer

Other modifications are available upon application and product review. Multiple modifications within a single unit may also be available.

Application specific mounted bearing modification capabilities include:



High temperature applications

 Designed especially for use in temperatures ranging from 215° to 400° F




Low temperature applications

 Designed especially for use in temperatures ranging from -20° to -40° F



Air handling applications





Local Manufacturing Video



Dodge Industrial, Inc.

1061 Holland Road, Simpsonville, SC 29681 +1 864 297 4800

dodgeindustrial.com

Dodge Industrial, Inc. reserves all rights in this document and in the subject matter and illustrations contained therein. We reserve the right to modify contents without prior notice and do not accept responsibility for potential errors or possible lack of information in this document. Any reproduction, disclosure to third parties or utilization of its contents–in whole or in parts–is forbidden without prior written consent of Dodge Industrial, Inc.

© Copyright Dodge Industrial, Inc. All rights reserved. Specifications subject to change without notice. An RBC Bearings company.