

Supplement for Quantis A3 Incline mounting breather locations

These instructions must be read thoroughly before installing or operating this product. The instruction manual was correct at the time of printing. Please see dodgeindustrial.com for updated instruction manual.

WARNING: To ensure the drive is not unexpectedly started, turn off and lock-out or tag power source before proceeding. Failure to observe these precautions could result in bodily injury.

WARNING: All products over 25 kg (55 lbs) are noted on the shipping package. Proper lifting practices are required for these products.


WARNING: Because of the possible danger to person(s) or property from accidents which may result from the improper use of products, it is important that correct procedures be followed. Products must be used in accordance with the engineering information specified in the catalog. Proper installation, maintenance and operation procedures must be observed. The instructions in the instruction manuals must be followed. Inspections should be made as necessary to assure safe operation under prevailing conditions. Proper guards and other suitable safety devices or procedures as may be desirable or as may be specified in safety codes should be provided, and are neither provided by Dodge nor are the responsibility of Dodge. This unit and its associated equipment must be installed, adjusted and maintained by qualified personnel who are familiar with the construction and operation of all equipment in the system and the potential hazards involved. When risk to persons or property may be involved, a holding device must be an integral part of the driven equipment beyond the speed reducer output shaft.

Introduction


All gearboxes are shown from the output shaft side. All recommendations provide the minimum breather requirement. When space allows, always use breather kit and extension that provides maximum breather height.

Breather kits were validated through full load laboratory testing for 0 – 20 degree incline/decline applications.

0°-20° Clockwise and
0°-5° Counter Clockwise



6°-20° Counter
Clockwise



Dodge Industrial, Inc.
1061 Holland Road
Simpsonville, SC 29681
+1 864 297 4800

